

New Holland BB-A Big Baler Specifications



BB940A Standard BB940A Packer Cutter BB940A Rotor Cutter BB960A Standard BB960A Rotor Cutter

| MODEL | BB940A Standard | BB940A Packer Cutter | BB940A Rotor Cutter | BB960A Standard | BB960A Rotor Cutter |
|-------------------------------------|---------------------------------------|------------------------------------|-----------------------------------|------------------------------------|------------------------------------|
| Approximate Bale Dimensions: | | | | | |
| Width | 31.5 in. (800 mm) | 31.5 in. (800 mm) | 31.5 in. (800 mm) | 47.3 in. (1200 mm) | 47.3 in. (1200 mm) |
| Height |35.4 in. (900 mm) | | | | |
| Length |98.4 in. (2500 mm) maximum..... | | | | |
| Pickup | | | | | |
| Operating width | 78.1 in. (1982 mm) | 78.1 in. (1982 mm) | 78.8 in. (2000 mm) | 88.4 in. (2246 mm) | 94.5 in. (2400 mm) |
| Number of tines | 56 double (112) | 56 double (112) | 56 double (112) | 64 double (128) | 68 double (136) |
| Protection |Slip and overrunning clutch..... | | | | |
| Pickup lift |Hydraulic..... | | | | |
| Pickup flotation |Adjustable spring..... | | | | |
| Feeder | | | | | |
| Packer/Rotor | Packer: 2 forks, 6 single tines | Packer: 3 forks, 6 double tines | Rotor: width 38.3 in. (972 mm) | Packer: 3 forks, 9 single tines | Rotor: width 53.7 in. (1356 mm) |
| Protection | Slip clutch | Slip clutch | Cut-out clutch | Slip clutch | Cut-out clutch |
| Pre-Cutting System | | | | | |
| Maximum number of knives | NA | 6 | 23 | NA | 33 |
| Theoretical average cut length | NA | 4.5 in (114 mm) | 1.5 in (39 mm) | NA | 1.5 in (39 mm) |
| Pre-Compression Chamber | | | | | |
| Stuffer | Fork-type with 4 tines | Fork-type with 6 tines | Fork-type with 4 tines | Fork-type with 6 tines | Fork-type with 6 tines |
| Width | 31.5 in (800 mm) | 31.5 in (800 mm) | 31.5 in (800 mm) | 46.6 in (1184 mm) | 46.6 in (1184 mm) |
| Bale Chamber and Plunger | | | | | |
| Plunger speed |42 strokes/min..... | | | | |
| Length of stroke |27.9 in (710 mm)..... | | | | |
| Tying Mechanism | | | | | |
| Knotters | Four double-knot type | Four double-knot type | Four double-knot type | Six double-knot type | Six double-knot type |
| Twine capacity |30 balls..... | | | | |
| Tractor Requirements | | | | | |
| Minimum tractor power | 102 hp (75 kW) | 110 hp (80 kW) | 130 hp (95 kW) | 125 hp (90 kW) | 150 hp (110 kW) |
| Minimum weight | 13,228 lb (6,000 kg) | 13,228 lb (6,000 kg) | 13,228 lb (6,000 kg) | 15,433 lb (7,000 kg) | 15,433 lb (7,000 kg) |
| Hydraulics | 2 valves | 3 valves | 3 valves | 2 valves | 3 valves |

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.