

Bush Hog® TOUGH

The 4430 4x4

BUSH HOG® TOUGH FEATURES

- TOUGH Three-year Drive Train Limited Warranty
- TOUGH Sealed And Pressurized CVT Protection System
- TOUGH Double CV Joints At Each Wheel
- TOUGH Four Wheel Hydraulic Disc Brakes
- TOUGH Brush Guards Come In Three Styles



The Only Utility Vehicle Built Bush Hog® TOUGH

The new Bush Hog 4430 4 x 4 is built to work. With Bush Hog TOUGH Features that deliver traction that won't quit, load carrying capacity that won't quit and a smooth ride that won't quit.

STANDARD FEATURES

Every Bush Hog 4430 comes with standard features that help you get your job done. Standard features include:

- Two-inch hitch receivers front and rear
- Electric fuel gauge, hour meter, rocker switches
- 37-watt halogen headlights
- Tail and brake lights
- Under hood storage
- Glove box
- Two large cup holders
- Quiet, rust-proof high capacity poly bed or flat bed for easy loading, carrying and off loading of bulky items
- Occupant Protective System (OPS) with seatbelts

MODELS		4430
ENGINE		4 cycle, OHV V-twin, air-cooled gas
Make/HP (displacement)		Honda® 24 HP (670 CC)
Lubrication		Full Pressure with automotive style spin-on canister
Air Cleaner		Remote, 2 stage cyclone-type with replaceable dual elements
Electrical System		12 volt DC with 20 amp alternator
Battery		530 CCA rating@32 degrees F
CHASSIS		
Suspension, Front		MacPherson strut, Single A-arm, coil-over-shock
Suspension, Rear		Independent trailing arm, coil-over-shock
Wheel travel, Front/Rear		5.7 inches/6.0 inches
Steering		Rack and Pinion
Turning Radius		13 ft
Front Tires		AT 25 x 10.0 - 12 NHS
Rear Tires		AT 25 x 11.0 - 12 NHS
Brakes		4 wheel hydraulic disc brakes; self-adjusting with tandem master cylinder
Park Brake		Rear mechanical disc
Ground Clearance		9 inches
Under Foot Platform		13 1/2 inches
DRIVE TRAIN		
Transmission		Continuously Variable Transmission (CVT)
CVT Protection		Fully enclosed pressurized with filtered air intake
Final Drive		Bush Hog® Dual-Range transaxle with High, Low, Neutral and Reverse
Differential Lock		ruck-style automatic positive locking differential; featuring Detroit Gearless Locker™
Ground Speed		0 - 25 mph
2WD/4WD		True On-Demand 4 wheel drive
DIMENSIONS		
Dry Weight		1500 lbs
Wheel Base		76 inches
Track Width-Front		57 inches
Track Width-Back		58.5 inches
Overall Dimensions (LxWxH)		119 x 60 x 78 inches
Vehicle Load Capacity		1500 lbs
Cargo Box Load Capacity		1000 lbs
Cargo Box Dimensions (LxWxH)		44 x 56.5 x 13.4 inches
Flatbed Dimensions (LxW)		47.5 x 56.5
Towing Capacity		1500 lbs
Fuel Capacity		7 gallons
Seating Capacity (Bench-type)		3
Lights		Dual 37 watt halogen headlights, tail lights and brake lights
Colors		Classic Bush Hog® Red, Deep Forest Green and Mossy Oak Obsession® camouflage
Options		See Accessories Brochure
Warranty		1 year limited warranty. See dealer for complete details. 2 year engine limited warranty administered through engine manufacturers. 3-year drive train limited warranty

BUSH HOG EXCLUSIVE: Patented Sealed and Pressurized CVT Protection System

Products in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, require attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation.



BUSH HOG®
Performance You Can Count On™

www.bushhog.com

Bush Hog®, L.L.C.
P.O. Box 1039 Selma, AL 36702-1039
(334) 874-2700

©May 2008 Bush Hog, LLC