

# Specifications

Model	BR7050	BR7050 High-Moisture	BR7060 Standard	BR7060	BR7060 Silage Special	BR7060 CropCutter®
<b>Bale Size</b>						
Diameter, in. (cm)	30–48 (76–122)	30–48 (76–122)	36–60 (92–152)	36–60 (92–152)	36–60 (92–152)	36–60 (92–152)
Width, in. (cm)	46.5 (118)	46.5 (118)	46.5 (118)	46.5 (118)	46.5 (118)	46.5 (118)
Weight, lbs. (kg)	300–750 (136–340)	400–1000 (181–454)	400–1200 (181–544)	400–1200 (181–544)	400–1800 (181–816)	400–1800 (181–816)
Density pressure	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
<b>Baler Dimensions and Weight</b>						
Overall width, in. (cm)	85 (216)	85 (216)	85 (216)	95 (240)	95 (240)	95 (240)
Overall length (tailgate closed), in. (cm)	135 (343)	135 (343)	185 (470)	185 (470)	185 (470)	185 (470)
Overall length (tailgate open), in. (cm)	142 (361)	142 (361)	192 (488)	192 (488)	192 (488)	192 (488)
Overall height (tailgate closed), in. (cm)	85 (216)	86 (218)	116 (295)	116 (295)	116 (295)	116 (295)
Overall height (tailgate open), in. (cm)	127 (323)	127 (323)	158 (401)	158 (401)	158 (401)	158 (401)
Shipping weight, lbs. (kg)	2950 (1338)	3015 (1368)	4520 (2050)	5050 (2291)	5615 (2547)	6505 (2951)
<b>Super Sweep™ Pickup</b>						
Overall width, in. (cm)	60 (152)	60 (152)	60 (152)	NA	NA	NA
Width tine-to-tine, in. (cm)	45 (113)	45 (113)	45 (113)	NA	NA	NA
Width flare-to-flare, in. (cm)	53 (134)	53 (134)	53 (134)	NA	NA	NA
Tine spacing, in. (cm)	2.6 (7)	2.6 (7)	2.6 (7)	NA	NA	NA
Tine bars	4	4	4	NA	NA	NA
Number of tines	72	72	72	NA	NA	NA
Reel diameter, in. (cm)	16 (41)	16 (41)	16 (41)	NA	NA	NA
Pickup protection	Adjustable slip clutch	Adjustable slip clutch	Adjustable slip clutch	NA	NA	NA
<b>Wide Pickup</b>						
Overall width, in. (cm)	NA	NA	NA	77 (194)	77 (194)	NA
Width tine-to-tine, in. (cm)	NA	NA	NA	60 (153)	60 (153)	NA
Width flare-to-flare, in. (cm)	NA	NA	NA	69 (174)	69 (174)	NA
Tine spacing, in. (cm)	NA	NA	NA	2.6 (7)	2.6 (7)	NA
Tine bars	NA	NA	NA	4	4	NA
Number of tines	NA	NA	NA	96	96	NA
Reel diameter, in. (cm)	NA	NA	NA	10 (25)	10 (25)	NA
Pickup protection	NA	NA	NA	Adjustable ratchet clutch	Adjustable ratchet clutch	NA
<b>XtraSweep™ Pickup (1.8M)</b>						
Overall width, in. (cm)	NA	NA	NA	84 (213)	84 (213)	NA
Width tine-to-tine, in. (cm)	NA	NA	NA	71 (181)	71 (181)	NA
Width flare-to-flare, in. (cm)	NA	NA	NA	79 (201)	79 (201)	NA
Tine spacing, in. (cm)	NA	NA	NA	2.6 (7)	2.6 (7)	NA
Tine bars	NA	NA	NA	4	4	NA
Number of tines	NA	NA	NA	112	112	NA
Reel diameter, in. (cm)	NA	NA	NA	12 (31)	12 (31)	NA
Pickup protection	NA	NA	NA	Adjustable ratchet clutch	Adjustable ratchet clutch	NA
<b>XtraSweep™ Pickup (2.07M)</b>						
Overall width, in. (cm)	NA	NA	NA	NA	NA	94 (240)
Width tine-to-tine, in. (cm)	NA	NA	NA	NA	NA	82 (207)
Width flare-to-flare, in. (cm)	NA	NA	NA	NA	NA	90 (228)
Tine spacing, in. (cm)	NA	NA	NA	NA	NA	2.6 (7)
Tine bars	NA	NA	NA	NA	NA	4
Number of tines	NA	NA	NA	NA	NA	128
Reel diameter, in. (cm)	NA	NA	NA	NA	NA	12 (31)
Pickup protection	NA	NA	NA	NA	NA	Shearbolt

Model	BR7050	BR7050 High-Moisture	BR7060 Standard	BR7060	BR7060 Silage Special	BR7060 CropCutter®
<b>Bale Forming Chamber</b>						
Floor roll, in. (cm)	12 (31)	12 (31)	12 (31)	12 (31)	12 (31)	12 (31)
Forming rolls, in. (cm)	2 rolls, 10 (25)	2 rolls, 10 (25)	3 rolls, 10 (25)	3 rolls, 10 (25)	3 rolls, 10 (25)	3 rolls, 10 (25)
Stripper roll	Embossed surface	Embossed surface	Embossed surface	Embossed surface	Embossed surface	Embossed surface
Starter roll, in. (cm)	Embossed surface	Embossed surface	7 (17)	7 (17)	7 (17)	7 (17)
Steel looped sledge follower roll	NA	NA	NA	NA	Standard	Standard
Tailgate nose roll	NA	Standard	NA	NA	Standard	Standard
Rubber backwrap roll	NA	Standard	NA	NA	Standard	Standard
<b>Belts</b>						
Number of belts	6	6	6	6	6	6
Width, in. (cm)	7 (18)	7 (18)	7 (18)	7 (18)	7 (18)	7 (18)
Length, in. (cm)	273 (692)	273 (692)	343 (871)	343 (871)	343 (871)	343 (871)
Surface	Mini-rough top	Mini-rough top	Mini-rough top	Mini-rough top	Mini-rough top	Mini-rough top
Endless belts	NA	NA	NA	NA	Standard	Standard
<b>Twine System</b>						
Twine application	One pivoting arm	One pivoting arm	Dual pivoting arms	Dual pivoting arms	Dual pivoting arms	Dual pivoting arms
Twine control	Electric toggle switch	Electric toggle switch	Automatic	Automatic	Automatic	Automatic
Twine storage capacity	4 balls	4 balls	6 balls	6 balls	6 balls	6 balls
<b>EdgeWrap™</b>						
Net wrap	NA	NA	NA	Available	Available	Available
<b>Bale Forming Indicators</b>						
Bale size	Standard	Standard	Standard	Standard	Standard	Standard
Driving gauges	NA	NA	NA	Standard	Standard	Standard
Twine movement	Standard	Standard	Standard	Standard	Standard	Standard
Twine arm position	Standard	Standard	Standard	Standard	Standard	Standard
Bale counter	Standard	Standard	Standard	Standard	Standard	Standard
Bale ejector	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic pressure gauge	NA	NA	Standard	Standard	Standard	Standard
Tailgate latch	Standard	Standard	Standard	Standard	Standard	Standard
<b>Tractor Requirements</b>						
PTO hp (minimum), hp (kW)	40 (30)	45 (33)	60 (45)	60 (45)	65 (48)	100 (75)
PTO speed (rpm)	540	540	540	540	540	540
PTO protection	Shearbolt	Shearbolt	Shearbolt	Slip clutch	Slip clutch	Cutout clutch
Hydraulic remote requirement	1	1	1 - 2	1 - 2	1 - 2	3 - 4



# Specifications

Model	BR7070	BR7070 Silage Special	BR7070 CropCutter®	BR7080	BR7090
<b>Bale Size</b>					
Diameter, in. (cm)	36–72 (91.5–182)	36–72 (91.5–182)	36–72 (91.5–182)	36–60 (91.5–152)	36–72 (91.5–182)
Width, in. (cm)	46.5 (118)	46.5 (118)	46.5 (118)	61.5 (156)	61.5 (156)
Weight, lbs. (kg)	400–1650 (181–748)	400–2200 (181–998)	400–2200 (181–998)	500–1550 (227–703)	500–2200 (227–998)
Density pressure	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
<b>Baler Dimensions and Weight</b>					
Overall width, in. (cm)	95 (240)	95 (240)	95 (240)	111 (282)	111 (282)
Overall length (tailgate closed), in. (cm)	187 (475)	187 (475)	187 (475)	180 (457)	190 (483)
Overall length (tailgate open), in. (cm)	200 (508)	200 (508)	200 (508)	192 (488)	200 (508)
Overall height (tailgate closed), in. (cm)	126 (320)	126 (320)	126 (320)	108 (274)	124 (315)
Overall height (tailgate open), in. (cm)	175 (445)	175 (445)	175 (445)	146 (371)	170 (432)
Shipping weight, lbs. (kg)	5900 (2676)	6310 (2862)	7050 (3198)	5525 (2506)	6920 (3139)
<b>Super Sweep™ Pickup</b>					
Overall width, in. (cm)	NA	NA	NA	88 (224)	88 (224)
Width tine-to-tine, in. (cm)	NA	NA	NA	60 (153)	60 (153)
Width flare-to-flare, in. (cm)	NA	NA	NA	68 (174)	68 (174)
Tine spacing, in. (cm)	NA	NA	NA	2.6 (7)	2.6 (7)
Tine bars	NA	NA	NA	6	6
Number of tines	NA	NA	NA	144	144
Reel diameter, in. (cm)	NA	NA	NA	16 (41)	16 (41)
Pickup protection	NA	NA	NA	Adjustable slip clutch	Adjustable slip clutch
<b>Wide Pickup</b>					
Overall width, in. (cm)	77 (194)	NA	NA	NA	NA
Width tine-to-tine, in. (cm)	60 (153)	NA	NA	NA	NA
Width flare-to-flare, in. (cm)	69 (174)	NA	NA	NA	NA
Tine spacing, in. (cm)	2.6 (7)	NA	NA	NA	NA
Tine bars	4	NA	NA	NA	NA
Number of tines	96	NA	NA	NA	NA
Reel diameter, in. (cm)	10 (25)	NA	NA	NA	NA
Pickup protection	Adjustable ratchet clutch	NA	NA	NA	NA
<b>XtraSweep™ Pickup (1.8M)</b>					
Overall width, in. (cm)	84 (213)	84 (213)	NA	NA	NA
Width tine-to-tine, in. (cm)	71 (181)	71 (181)	NA	NA	NA
Width flare-to-flare, in. (cm)	79 (201)	79 (201)	NA	NA	NA
Tine spacing, in. (cm)	2.6 (7)	2.6 (7)	NA	NA	NA
Tine bars	4	4	NA	NA	NA
Number of tines	112	112	NA	NA	NA
Reel diameter, in. (cm)	12 (31)	12 (31)	NA	NA	NA
Pickup protection	Adjustable ratchet clutch	Adjustable ratchet clutch	NA	NA	NA
<b>XtraSweep™ Pickup (2.07M)</b>					
Overall width, in. (cm)	NA	NA	94 (240)	NA	94 (240)
Width tine-to-tine, in. (cm)	NA	NA	82 (207)	NA	82 (207)
Width flare-to-flare, in. (cm)	NA	NA	90 (228)	NA	90 (228)
Tine spacing, in. (cm)	NA	NA	2.6 (7)	NA	2.6 (7)
Tine bars	NA	NA	4	NA	4
Number of tines	NA	NA	128	NA	128
Reel diameter	NA	NA	12 (31)	NA	12 (31)
Pickup protection	NA	NA	Shearbolt	NA	Shearbolt