

Specifications

Model	BR7070	BR7070 Silage Special	BR7070 CropCutter®	BR7080	BR7090
Bale Size					
Diameter, in. (cm)	36–72 (91.5–182)	36–72 (91.5–182)	36–72 (91.5–182)	36–60 (91.5–152)	36–72 (91.5–182)
Width, in. (cm)	46.5 (118)	46.5 (118)	46.5 (118)	61.5 (156)	61.5 (156)
Weight, lbs. (kg)	400–1650 (181–748)	400–2200 (181–998)	400–2200 (181–998)	500–1550 (227–703)	500–2200 (227–998)
Density pressure	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Baler Dimensions and Weight					
Overall width, in. (cm)	95 (240)	95 (240)	95 (240)	111 (282)	111 (282)
Overall length (tailgate closed), in. (cm)	187 (475)	187 (475)	187 (475)	180 (457)	190 (483)
Overall length (tailgate open), in. (cm)	200 (508)	200 (508)	200 (508)	192 (488)	200 (508)
Overall height (tailgate closed), in. (cm)	126 (320)	126 (320)	126 (320)	108 (274)	124 (315)
Overall height (tailgate open), in. (cm)	175 (445)	175 (445)	175 (445)	146 (371)	170 (432)
Shipping weight, lbs. (kg)	5900 (2676)	6310 (2862)	7050 (3198)	5525 (2506)	6920 (3139)
Super Sweep™ Pickup					
Overall width, in. (cm)	NA	NA	NA	88 (224)	88 (224)
Width tine-to-tine, in. (cm)	NA	NA	NA	60 (153)	60 (153)
Width flare-to-flare, in. (cm)	NA	NA	NA	68 (174)	68 (174)
Tine spacing, in. (cm)	NA	NA	NA	2.6 (7)	2.6 (7)
Tine bars	NA	NA	NA	6	6
Number of tines	NA	NA	NA	144	144
Reel diameter, in. (cm)	NA	NA	NA	16 (41)	16 (41)
Pickup protection	NA	NA	NA	Adjustable slip clutch	Adjustable slip clutch
Wide Pickup					
Overall width, in. (cm)	77 (194)	NA	NA	NA	NA
Width tine-to-tine, in. (cm)	60 (153)	NA	NA	NA	NA
Width flare-to-flare, in. (cm)	69 (174)	NA	NA	NA	NA
Tine spacing, in. (cm)	2.6 (7)	NA	NA	NA	NA
Tine bars	4	NA	NA	NA	NA
Number of tines	96	NA	NA	NA	NA
Reel diameter, in. (cm)	10 (25)	NA	NA	NA	NA
Pickup protection	Adjustable ratchet clutch	NA	NA	NA	NA
XtraSweep™ Pickup (1.8M)					
Overall width, in. (cm)	84 (213)	84 (213)	NA	NA	NA
Width tine-to-tine, in. (cm)	71 (181)	71 (181)	NA	NA	NA
Width flare-to-flare, in. (cm)	79 (201)	79 (201)	NA	NA	NA
Tine spacing, in. (cm)	2.6 (7)	2.6 (7)	NA	NA	NA
Tine bars	4	4	NA	NA	NA
Number of tines	112	112	NA	NA	NA
Reel diameter, in. (cm)	12 (31)	12 (31)	NA	NA	NA
Pickup protection	Adjustable ratchet clutch	Adjustable ratchet clutch	NA	NA	NA
XtraSweep™ Pickup (2.07M)					
Overall width, in. (cm)	NA	NA	94 (240)	NA	94 (240)
Width tine-to-tine, in. (cm)	NA	NA	82 (207)	NA	82 (207)
Width flare-to-flare, in. (cm)	NA	NA	90 (228)	NA	90 (228)
Tine spacing, in. (cm)	NA	NA	2.6 (7)	NA	2.6 (7)
Tine bars	NA	NA	4	NA	4
Number of tines	NA	NA	128	NA	128
Reel diameter	NA	NA	12 (31)	NA	12 (31)
Pickup protection	NA	NA	Shearbolt	NA	Shearbolt

Model	BR7070	BR7070 Silage Special	BR7070 CropCutter®	BR7080	BR7090
Bale Forming Chamber					
Floor roll, in. (cm)	12 (31)	12 (31)	12 (31)	12 (31)	12 (31)
Forming rolls, in. (cm)	3 rolls, 10 (25)	3 rolls, 10 (25)	3 rolls, 10 (25)	3 rolls, 10 (25)	3 rolls, 10 (25)
Stripper roll	Embossed surface	Embossed surface	Embossed surface	Embossed surface	Embossed surface
Starter roll, in. (cm)	7 (17)	7 (17)	7 (17)	7 (17)	7 (17)
Steel looped sledge follower roll	NA	Standard	Standard	NA	NA
Tailgate nose roll	NA	Standard	Standard	NA	NA
Rubber backwrap roll	NA	Standard	Standard	NA	NA
Belts					
Number of belts	6	6	6	8	8
Width, in. (cm)	7 (18)	7 (18)	7 (18)	7 (18)	7 (18)
Length, in. (cm)	421 (1068)	421 (1068)	421 (1068)	343 (871)	421 (1068)
Surface	Mini-rough top	Mini-rough top	Mini-rough top	Mini-rough top	Mini-rough top
Endless belts	NA	Standard	Standard	NA	Optional
Twine System					
Twine application	Dual pivoting arms	Dual pivoting arms	Dual pivoting arms	Dual pivoting arms	Dual pivoting arms
Twine control	Automatic	Automatic	Automatic	Automatic	Automatic
Twine storage capacity	6 balls	6 balls	6 balls	6 balls	6 balls
EdgeWrap™					
Net wrap	Available	Available	Available	Available	Available
Bale Forming Indicators					
Bale size	Standard	Standard	Standard	Standard	Standard
Driving gauges	Standard	Standard	Standard	Standard	Standard
Twine movement	Standard	Standard	Standard	Standard	Standard
Twine arm position	Standard	Standard	Standard	Standard	Standard
Bale counter	Standard	Standard	Standard	Standard	Standard
Bale ejector	Standard	Standard	Standard	Standard	Standard
Hydraulic pressure gauge	Standard	Standard	Standard	Standard	Standard
Tailgate latch	Standard	Standard	Standard	Standard	Standard
Tractor Requirements					
PTO hp (minimum), hp (kW)	70 (52)	70 (52)	105 (78)	70 (52)	80 (60)
PTO speed (rpm)	540	540	540	540	540/1000
PTO protection	Slip clutch	Slip clutch	Cutout clutch	Slip clutch	Slip clutch
Hydraulic remote requirement	1 – 2	1 – 2	3 – 4	1 – 2	1 – 2

