

New Holland Rolabar Rake Specifications



57 256 258 260

MODEL	57	256	258	260
Raking width, ft. in. (mm)	8'6" (2591)	8'6" (2591)	9'6" (2896)	9'6" (2896)
Width overall, ft. in. (mm)	10'3" (3124)	10'3" (3124)	11' (3353)	11' (3353)
Height overall, ft. in. (mm)	3'4" (1016)	4'4" (1321)	4'4" (1321)	4'4" (1321)
Length overall, ft. in. (mm)	6'5" (1956)	10'1" (3073)	10'1" (3073)	10'1" (3073)
Wheel Tread, ft. in. (mm)	5'5" (1651)	5'6" (1676)	5'6" (1676)	5'6" (1676)
Transport Speed, mph (km/h)	Tractor Speed	20 (32)	20 (32)	20 (32)
Operating Speed, mph (km/h)	2 to 8 (3 to 13)	2 to 7 (3 to 11)	2 to 7 (3 to 11)	2 to 7 (3 to 11)
Weight, approx., lbs. (kg)	777 (352)	790 (358) less tires	850 (386) less tires	885 (401) less tires
Main frame, in. (mm)	3 (76) channel, cross-braced with heavy tubular members4 (102) channel, cross-braced with heavy tubular membersOn hydraulic models-2 to 10 (3 to 16)
Basket	—One piece; welded heavy steel angle
Gearbox(ground drive)	NoneHeat-treated gears and clutch running in grease on tapered roller bearings
Drive Housing	Special accuracy shaft running on tapered roller bearings	None	None	None
Tine bars5, standard high carbon5, extra-heavy high carbon5, extra-heavy high carbon5, extra-heavy high carbon
TinesSteel or rubber-mountedSteel or rubber-mountedSteel or rubber-mounted	Rubber-mounted
Number of tines	90	90	100 or 155	100 or 155
Tine Bar Bearings	Single ball bearing	Single ball bearing	Double ball bearing	Double ball bearing
Drive	PTO	Ground	Ground or hydraulic	Ground or hydraulic
Delivery	Left-hand	Left-hand	Left-hand	Right-hand

COMPLETING PACKAGES AND OPTIONS:

- Hitch and jack
- Dolly wheels
- 5.00 x 15 wheels/tires
- 27 x 9.50-15 Rib implement tires
- 15" wheels only
- Flow control kit for single hydraulic rake
- Dual wheel attachment
- Stripper bar support
- Wide tire adapter
- Safety chain and hardware