

New Holland G Series Zero-Turn-Radius Mower Specifications



G4010 G4020 G4030

MODELS	G4010	G4020	G4030
ENGINE			
Horsepower, hp (kW)	19 (14.2)	21 (15.7)	23 (17.2)
Make	Kohler Courage SV590	Kohler Courage SV610	Kohler Courage SV720
No. of cylinders	1	1	2
Cooling system	Air		
Fuel capacity, gal. (L)	3 (11.4)		
Full pressure lubrication	Standard		
Starter key w/safety interlock	Standard		
Air cleaner, dual element	Standard		

DRIVE SYSTEM

Type	Dual hydrostatic: transaxle with integral pump and motor; one at each wheel		
Max speed, forward, mph (kph)	7.0 (11.3)		
Max speed, reverse, mph (kph)	3.4 (5.5)		
Implement clutch	Electric		

BRAKES

Service brake	Hydrostatic dynamic braking		
Parking brake Lock	Automatic engagement with steering levers in neutral		

ELECTRICAL

Voltage	12 volts		
Charging system (amps)	15		
Battery, cca	195		

OPERATOR STATION AND CONTROLS

Steering	Dual padded lever hydrostatic with hydraulic dampening		
Seat type	Contoured, high back, adjustable fore and aft		
Armrests	Optional	Optional	Standard
Cup holder	Standard		
Storage bin	Standard		
Front casters	Double yoke		

WHEELS AND TIRES

Front Casters	10 x 4 ribbed	10 x 4 smooth	10 x 4 smooth
Rear	18 x 7.5-8, 2-ply		

DIMENSIONS, IN. (CM)

Length, overall			
with grass catcher	90.0 (228.6)		
less grass catcher	73.1 (185.7)		
Width, overall			
with deck deflector down	53.8 (136.7)	63.0 (160.0)	63.0 (160.0)
with deck deflector up	46.0 (116.8)	53.5 (135.9)	53.5 (135.9)
with grass catcher	52.8 (134.1)	56.8 (144.3)	56.8 (144.3)
Height, overall, to top of seat	37.2 (94.5)	40.2 (102.1)	40.2 (102.1)
Wheelbase	48.1 (122.2)		
Turning radius, inside rear wheel	Zero turn		
Net weight, estimated, lb. (kg)	500 (226.8)	552 (250.4)	565 (256.3)

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

New Holland G Series Zero-Turn-Radius Mower Specifications



G4010 G4020 G4030

MODELS	G4010	G4020	G4030
MOWER DECKS (optional mulching kits available)			
42 in. side discharge	Standard	—	—
50 in. side discharge	—	Standard	Standard
Spindles	2	3	3
Anti-scalp gauge wheels	Standard		
ATTACHMENTS & ACCESSORIES			
2-bag grass catcher (8 cu. ft.).....	Optional.....		
56-inch front blade	N/A.....		
Rear engine guard	Optional	Standard	Standard
Engine top cover	Optional.....		
Foot assist height of cut kit	Optional	Optional	Standard
Smooth-tread front tires	Optional	Standard	Standard

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.