

New Holland MC Commercial Front Mowers Specifications



MC22 MC28 MC35

MODEL	MC22	MC28	MC35
GROSS HORSEPOWER	22	28	35
ENGINE			
Engine type.....		Diesel.....	
Number of cylinders.....		3.....	
Displacement, cu. in. (L).....	61.3 (1.0)	81.1 (1.3)	101.4 (1.7)
Air cleaner.....		Dry, dual element.....	
Fuel tank capacity, gal. (L).....		13.3 (50.0).....	
ELECTRICAL			
Voltage.....		12.....	
Alternator.....		40 amp.....	
Battery.....		490 cca.....	
TRANSMISSION			
Type.....		Hydrostatic.....	
Ranges.....		2.....	
Speed ranges (with standard tire), mph (kph)			
Low forward.....		0-6.1 (0-9.8).....	
Low reverse.....		0-4.0 (0-6.4).....	
High forward.....		0-10.7 (0-17.2).....	
High reverse.....		0-7.0 (0-11.3).....	
FRONT AXLE			
Type.....		Flanged.....	
Differential lock.....		Standard.....	
Brake.....		Wet disc.....	
Tread width (with standard tire), in. (cm).....		37.0 (94).....	
2WD Rear axle	Optional	Optional	N/A
Tread width (with standard tire), in. (cm).....		39 (99.0).....	
Turning radius, in. (cm).....		28.7 (72.9).....	
Turning angle.....		57°.....	
Oscillation.....		9°.....	
4WD Rear axle	Optional	Optional	Standard
Drive type.....		Automatic or full-time.....	
Tread width (with standard tire), in. (cm).....		39.2 (99.6).....	
Turning radius, in. (cm).....		29.5 (74.9).....	
Turning angle.....		56°.....	
Oscillation.....		8°.....	
STEERING			
Type.....		Hydrostatic power.....	
PTO			
Type.....		Independent.....	
Speed (at engine rated speed).....		2209 rpm.....	
Engagement.....		Mechanical.....	
HYDRAULIC SYSTEM			
Type.....		Open center.....	
Pump capacity, gpm (lpm).....	1.9 (7.2)	2.4 (9.1)	2.4 (9.1)
Remote valve.....		Optional.....	

New Holland MC Commercial Front Mowers Specifications



MC22 MC28 MC35

MODEL	MC22	MC28	MC35
TRACTOR DIMENSIONS (with standard tires), in. (cm)			
Overall length		95.1 (241.6)	
Height (ROPS up)		76.0 (193.0)	
Height (ROPS down)		48.2 (122.4)	
Minimum overall width		48.0 (121.9)	
Minimum ground clearance		5.5 (13.9)	
Wheelbase		49.2 (124.9)	
WEIGHT, lbs. (kg)			
2WD	1550 (703.1)	1570 (712.1)	N/A
4WD	1630 (739.4)	1650 (748.4)	1650 (748.4)
OPTIONAL ATTACHMENTS AND ACCESSORIES			
24 cu. ft. grass catcher	X	X	X
60 in. side discharge rotary mower	X	X	X
60 in. rear discharge mulching mower	X	X	X
72 in. side discharge rotary mower	X	X	X
72 in. rear discharge mulching mower	X	X	X
84 in. rear discharge mulching mower	X	X	X
60 in. rear discharge flail mower	X	X	X
60 in. front quick-attach blade	X	X	X
60 in. front quick-attach rotary broom	X	X	X
Front quick-attach debris blower	X	X	X
52 in. front quick-attach snow blower	X	X	X
62 in. front quick-attach snow blower	X	X	X
4 post ROPS with canopy	X	X	X
Comfort soft cab	X	X	X

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

 **NEW HOLLAND IS A BRAND OF CNH.**
A GLOBAL LEADER IN AGRICULTURAL AND CONSTRUCTION EQUIPMENT AND FINANCIAL SERVICES.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.